



All dimensions are nominal. Illustration may be shown with optional equipment.

Standard Features

Hitch/Tongue

- Adjustable height, bolt-on coupler
- 2.5" pintle
- 7-Pole RV Plug
- One-piece cold-formed I-Beam frame rails
- Integrated storage tray (lid optional)
- 12K bolt-on side-wind, drop-leg parking jack
- Battery break-away kit with tow charger & test light
- Safety chains with hooks

Frame/Deck

- 82" load width, 18.5" deck height (fully loaded)
- Deck cushion cylinder
- Dual-point, single lever deck lock
- 6" I-beam main frame
- 3" channel crossmembers
- 2" nominal white oak deck
- D-ring tie-downs (4 per side)
- 12 gauge one-piece formed fender/panel

Ramps/Tail

- 24" knife edge approach plate (24" length is in addition to 16' or 18' deck length)
- 12°/11° load angle

Axles/Suspension

- Rubber-ride Torsion suspension axles
- (2) 7,000 lb. axles (4 wheels)
- Tires - 235/85R16, load range F, 12-ply
- 16" wheels, 8-bolt
- Electric brakes
- Forward self-adjusting brakes
- EZ Lube hubs

Lights/Wiring

- Rubber grommet mounted LED lights
- Sealed modular wiring harness

Standard Features

- Limited Lifetime Frame Warranty-10 years
- One-Year full Warranty
- 11 Year Suspension Warranty
- Weatherproof registration holder
- Two-component polyurethane primer and paint
- Trailer color: Equipment Black

Weights and capacities vary depending upon options. Published weights are reference only.

GAWR (lbs)	GVWR (lbs)	Weight (lbs)	Capacity (lbs)	Deck Width (in)	Deck Length (ft)
14,000	15,820	3,820	12,000	82"	16'
14,000	16,120	4,120	12,000	82"	18'

Other options may be available. Ask your dealer or visit our website.

towmaster.com

800-462-4517

©Monroe Towmaster, LLC - 11.15.23 v1